

Integrity Operating Windows

API RECOMMENDED PRACTICE 584
SECOND EDITION, DECEMBER 2021



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

	Page
1 Purpose and Scope	1
2 Normative References	2
3 Terms and Definitions	2
4 Parameters that May Require Different Types and Levels of IOWs	5
5 IOW Work Process	7
6 IOW Risk Ranking	11
7 Examples of IOWs	13
8 IOW Development	17
9 General Considerations for Establishing IOWs and Their Limits	20
10 Documenting, Implementing, and Training on Established IOWs	22
11 Monitoring and Measuring IOW Parameters	24
12 Updating IOWs	25
13 Roles, Responsibilities, and Accountabilities for IOWs	25
14 Integrating IOWs with Other Related Work Processes	26
Annex A (informative) Examples of Potential Process Parameters for IOWs for Generic Process Units	27
Annex B (informative) Sample Format for Recording IOWs	53
Annex C (informative) Example of an IOW Development for a Heat Exchanger	54
Annex D (informative) Barriers to Successful IOW Implementation	56
Bibliography	58

Figures

1 Zones of Operation Including Target Ranges with Standard and Critical Limits	7
2 Example IOW Development Work Process	8
3 Generic Risk Matrix for Assessing IOW Levels	12
4 Example Risk Chart for IOW Types/Actions/Guidance	13
5 Example of IOW Limits for HTHA in a Hydroprocessing Unit	13
6 Examples of Different Levels of IOWs	14

Contents

Page

Tables

1	Examples of Accelerated Corrosion Rates That Can Occur Under Some Circumstances	21
A.1	Example IOWs for Crude Distillation Unit (Atmospheric and Vacuum Distillation)	28
A.2	Example IOWs for Catalytic Reformer Unit	32
A.3	Example IOWs for Hydroprocessing Unit	33
A.4	Example IOWs for FCC Unit and Gas Plant	36
A.5	Example IOWs for HF Acid Alkylation Unit	39
A.6	Example IOWs for Sulfuric Acid Alkylation Unit	39
A.7	Example IOWs for Delayed Coker Unit	41
A.8	Example IOWs for Steam Methane Reformer (Hydrogen Manufacturing) Unit	44
A.9	Example IOWs for Amine Unit	45
A.10	Example IOWs for Sour Water Stripper Unit.....	46
A.11	Example IOWs for Sulfur Recovery Unit.....	47
A.12	Example IOWs for Ethane Cracking Units.....	48
A.13	Example IOWs for Boiler Water Treatment and Return Condensate Quality	50
A.14	Example IOWs for Fired Heaters	51
B.1	Sample Format for Recording IOWs.....	53

Introduction

In today's operating environment, it is not enough to base future inspection plans only on prior recorded/known history of equipment condition. A fundamental understanding of the process/operating conditions and resulting damage mechanisms are required to establish and maintain an inspection program that yields the highest probability of detecting damage. Inspection plans should be dynamic and account for changing process conditions and current equipment condition. A fundamental step is to frequently rationalize and align the developed degradation knowledge base of the materials of construction with the operation of the equipment, its inspection history, measured corrosion rates and known industry problems. Whether utilizing time-based or risk-based methodology for determining inspection intervals, Integrity Operating Windows (IOWs) are useful to identify and track process information that either validates or might cause changes to existing inspection plans.

In order to maintain the integrity and reliability of pressure equipment in industry, multiple process safety management (PSM) systems may be necessary. Many of those management systems are oriented toward having a rigorous inspection program, as well as the supportive engineering activities. This may include the implementation of IOWs which can supplement process safety and inspection programs by identifying key process parameters potentially affecting mechanical integrity.

In addition to the application of industry codes, standards, and recommended practices, several other PSM systems are vital to support a rigorous inspection and mechanical integrity program to predict/avoid/prevent pressure equipment damage/corrosion; leaks and failures; and improve reliability. Three key elements of those supporting PSM programs include:

- the establishment, implementation, and maintenance of IOWs. See 3.6;
- an effective transfer of knowledge about unit specific IOWs to all affected personnel; and
- an effective MOC program to identify any changes to the process or the physical hardware that might affect the integrity of pressure equipment.

To operate any process unit, a set of operating ranges and limits should be established for key process variables, to achieve the desired results (i.e. product within specification, safe operation, reliability, etc.). These limits are generally called operating limits or operating envelopes. IOWs are a specific subset of these key operating limits that focus only on maintaining the integrity or reliability of process equipment. Typically, IOWs address issues that involve process variables that, when not adequately monitored or controlled, can impact the likelihood and rates of damage mechanisms, which may result in a loss of containment.

For purposes of this document, maintaining the integrity of the process unit means avoiding breaches of containment, and reliability means avoiding malfunctions of the pressure equipment that might impact the performance of the process unit (meeting its intended function for a specified time frame). In that sense, integrity is a part of the larger issue of pressure equipment reliability, since most breaches of containment will impact reliability. IOWs are those preset limits on process variables that need to be established and implemented to prevent potential breaches of containment that might occur as a result of not controlling the process sufficiently to avoid unexpected or unplanned deterioration or damage to pressure equipment. Operation within the preset limits should result in predictable and reasonably low rates of degradation. Operation outside the IOW limits could result in unanticipated damage, accelerated damage and potential equipment failure from one or more damage mechanisms.

Pressure equipment is generally fabricated from the most economical materials of construction to meet specific design criteria based on the intended operation and process conditions. The operating process conditions should then be controlled within preset limits (IOWs) to avoid unacceptable material degradation and achieve the desired economic design life of the assets.

Inspection plans are typically based on historic damage mechanisms and trends and are not generally designed to look for unanticipated damage resulting from process variability and upsets. Inspection plans generally assume that

the next inspection interval (calculated based on prior damage rates from past operating experience) are scheduled based on what is already known and predictable about equipment degradation from previous inspections. Without a set of effective and complete IOWs and feedback loop into the inspection planning process, inspections might need to be scheduled on a more frequent interval just to look for anything that might potentially occur from process variability. The owner-operator should implement and maintain an effective program for creating, establishing, and monitoring integrity operating windows. IOWs are implemented to avoid process parameter exceedances that may have an unanticipated impact on pressure equipment integrity.

Integrity Operating Windows

1 Purpose and Scope

1.1 The purpose of this recommended practice (RP) is to explain the importance of IOWs for process safety management and to guide users in how to establish and implement an IOW program for process facilities. Its express purpose is to minimize unexpected equipment degradation that could lead to loss of containment. It is not the intent of this document to provide a complete list of specific IOWs or operating variables that might need IOWs for the numerous types of process units in the industry (though some examples are provided in the text and a list of process variables for some example process units is included in Annex A); but rather to provide the user with information and guidance on the work process for development and implementation of IOWs to help strengthen the Mechanical Integrity (MI) program for each process unit.

The key goals of an IOW program are:

- 1) Defining IOW limits which will result in predictable and acceptable levels of equipment degradation to meet reliability expectations.
- 2) Enabling effective communication of equipment limits and exceedances between key Process, Operations, Maintenance, and other MI stakeholders to facilitate safe and reliable process operation and management.
- 3) Facilitating the reliable operation of equipment without loss of containment or the need for unplanned maintenance activities between scheduled outage or shutdowns.

1.2 The scope of this standard includes:

- definitions of IOWs and related terminology;
- creating and establishing IOWs;
- data and information typically needed to establish IOWs;
- descriptions of the various types and levels of IOWs needed for process parameters;
- risk ranking IOWs;
- documenting and implementing IOWs;
- monitoring and measuring process variables within established IOWs;
- communication of IOW exceedances;
- reviewing, changing, and updating IOWs;
- integrating IOWs with other risk management practices;
- roles and responsibilities in the IOW work process; and
- knowledge transfer to affected personnel.

1.3 This RP outlines the key elements in defining, monitoring, and maintaining IOWs as a vital component of integrity management (materials degradation control) and assisting in the inspection planning process, including Risk-Based Inspection (RBI). Other Process Safety systems may be affected by or involved with the IOW program, including management of change (MOC), process safety information (PSI), and training. For purposes of this RP, these systems are only addressed to the extent of mentioning the integration aspects that are needed with the IOW program.